

# Firestone Building Products Company

## Material Safety Data Sheet

January 26, 2009

Page: 1

---

### SECTION 1: PRODUCT IDENTIFICATION

---

Product Name: 18" QuickSeam™ SA Flashing  
Chemical Name / Synonym: None  
Chemical Family: Mixture  
24-Hour Emergency Phone: (800) 424-9300 CHEMTREC  
Manufacturer's Name: Firestone Building Products Company  
Manufacturer's Address: 250 West 96<sup>th</sup> Street, Indianapolis, IN 46260  
NFPA Hazard Rating: Health 1, Flammability 1, Reactivity 0  
HMIS Hazard Rating: Health 0, Flammability 1, Reactivity 0

---

### SECTION 2: CHEMICAL COMPOSITION

---

Chemical Name:	Common Name:	CAS #:	% (by wt)	Exposure Limits:
Nonhazardous as per 29 CFR 1910.1200	None	None	100	None Established

---

### SECTION 3: HAZARD IDENTIFICATION

---

Primary Route of Exposure: Eye contact  
Signs and Symptoms of Exposure: Contact with eye may result in irritation, redness, tearing and blurred vision.  
Medical Conditions Aggravated by Exposure: None known.  
Chronic Effects: No known adverse effects.  
Carcinogenicity: None.

---

### SECTION 4: FIRST AID MEASURES

---

First Aid Procedures: Treat as a foreign object in eye. Flush large amounts of water, frequently flushing under the lids. Get medical attention if irritation persists.

---

### SECTION 5: FIRE FIGHTING PROCEDURES

---

Suitable Extinguishing Media: Foam, water, dry chemical, or carbon dioxide.  
Hazardous Combustion Products: Carbon dioxide and carbon monoxide, oxides of nitrogen, sulfur dioxide, partially burned carbon.  
Recommended Fire Fighting Procedures: Treat as a Class "B" fire. Limit fire fighting to those trained to do so. Minimize breathing gases, vapor, fumes, or decomposition products. Use supplied air breathing equipment for enclosed or confined spaces or as otherwise needed.  
Unusual Fire and Explosion Hazards: None known.

# Firestone Building Products Company

## Material Safety Data Sheet

January 26, 2009

Page: 2

---

### SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

---

Steps to Be Taken in Case Material is Released or Spilled:	Shovel or scoop into a sealable container for disposal.
Precautions to Be Taken in Handling and Storing:	Do not store or handle at temperatures in excess of 130°F. Store in a cool, dry area. Avoid prolonged or repeated contact with the skin. Product readily removed from the skin with waterless hand cleaners followed by washing with soap and water.

---

### SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Ventilation:	No special ventilation requirements.
Respiratory Protection:	None required
Eye Protection:	Safety glasses with side shields may be necessary when handling, cutting or applying this product.
Skin Protection:	None required.
Other:	None required.
Work / Hygienic Practices:	Wash exposed skin prior to eating, drinking or smoking and at the end of each work shift. Wash contaminated clothing prior to reuse.

---

### SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance and Odor:	Black solid (EPDM) laminated to tape. No odor.		
Flash Point:	>200°C	Lower Explosive Limit:	None
Method Used:	Estimate based on the flash point of the most volatile component.	Upper Explosive Limit:	None
Evaporation Rate:	Not Applicable	Boiling Point:	None
pH (undiluted product):	Not Applicable	Melting Point:	Unknown
Solubility in Water:	None	Specific Gravity:	0.97 (Water=1)
Vapor Density:	Not Applicable	Percent Volatile:	0.7% Maximum
Vapor Pressure:	Not Applicable		

---

### SECTION 9: STABILITY AND REACTIVITY

---

Thermal Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	Exposure to temperature in excess of 130°F.

---

### SECTION 10: TRANSPORTATION

---

Regulatory Agency:	Not Regulated
Proper Shipping Name:	Not Applicable
Hazard Classification:	Not Applicable
Identification Number:	Not Applicable
Labels Required:	Not Applicable

# Firestone Building Products Company

## Material Safety Data Sheet

January 26, 2009

Page: 3

---

Other Requirements: Not Applicable

---

### SECTION 11: MISCELLANEOUS INFORMATION

---

Additional Comments: This product is considered to be a finished article as per 29 CFR 1910.1200(C) and is therefore exempt from the requirements of the Hazard Communication standard.

Date of Previous MSDS: June 26, 2008

Changes Since Previous MSDS: Company name change

Telephone Number for Additional Information: (317) 575-7190

---

### DISCLAIMER

---

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, a subsidiary of Firestone Diversified Products, LLC, assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.