

Section 1 - Product and Company Identification

Hazard Label DANGER label

Company InformationJohns Manville
Roofing Systems
P.O. Box 5108
Denver, CO 80127 USATelephone: 303-978-2000 8:00AM-5:00PM M-F
Internet Address: <http://www.jm.com>
Emergency: 800-424-9300 (Chemtrec, In English)

Trade Names: JM Single Ply Cleaner Low VOC

Use: Used to clean PVC and TPO membranes

Section 2 - Hazards Identification**Emergency Overview**

DANGER: Extremely flammable liquid and vapor. Vapor may cause flash fire. Use water spray to cool materials in or near a fire. Fire may be difficult to extinguish. Vapors may travel, and can be ignited by a remote source.

Inhalation

Irritation of the upper respiratory tract, coughing, and congestion may occur in extreme exposures. Severe irritation of the mouth, nose, and throat, as well as signs of central nervous system depression (drowsiness, dizziness, headache), may occur upon inhalation of vapors or gases.

Skin

Drying of skin, dermatitis, and blistering may occur following prolonged exposures.

Ingestion

This product is not intended to be ingested under normal conditions of use. May be harmful if swallowed. May cause gastrointestinal irritation and disturbances. May cause effects similar to those for inhalation exposure. Aspiration into the lungs may cause lung inflammation and other lung injury.

Eyes

Irritation, redness, and burning in eyes may occur.

Primary Routes of Entry (Exposure)

Inhalation, skin, and eye contact.

Target Organs

Skin, eye, lungs, central nervous system (CNS), respiratory system, kidney, liver.

Medical Conditions Aggravated by Exposure

Pre-existing eye, skin, respiratory, central nervous system (CNS), liver and kidney diseases or conditions.

Section 3 - Composition/Information on Ingredients

CAS #	Component	Percent
67-64-1	Acetone	100

General Product Description

Flammable clear liquid.

Section 4 - First Aid Measures**First Aid: Inhalation**

If the affected person is having difficulty breathing, administer oxygen or apply artificial respiration and immediately contact a medical professional.

First Aid: Skin

Remove contaminated clothing. Wash exposed areas with soap and water. If irritation develops or persists, seek medical attention. Launder contaminated clothing before reuse.

First Aid: Ingestion

Product is not intended to be ingested or eaten. If this product is ingested, do not induce vomiting and seek medical attention immediately.

First Aid: Eyes

Flush eyes with large amounts of water until irritation subsides. If irritation persists, seek medical attention.

First Aid: Notes to Physician

Treatment for inhalation, skin contact, or ingestion should be symptomatic. Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias.

Section 5 - Fire Fighting Measures**Flash Point:** -4F**Upper Flammable Limit (UFL):** 13.0**Auto Ignition:** 465°C**General Fire Hazards**

DANGER: EXTREMELY FLAMMABLE liquid and vapor.

Keep away from heat, sparks, and flame. Material is highly volatile and readily gives off vapors which are heavier than air and may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Keep container closed. Use with adequate ventilation.

Extinguishing Media

Carbon dioxide (CO₂), water, water fog, dry chemical.

Fire Fighting Equipment/Instructions

Use NIOSH-approved self-contained breathing apparatus operating in the pressure demand mode and full fire fighting protective clothing. Avoid inhalation of vapors.

Section 6 - Accidental Release Measures**Containment Procedures**

Remove all sources of ignition. Evacuate and ventilate spill area. Dam spill area with sand, earth, or other suitable absorbent. Prevent entry of material into sewers, other water sources, or land areas. Wear full protective clothing and respiratory protection during clean-up as required to maintain exposures below the applicable exposure limit. Shovel absorbed material into containers in well-ventilated area.

Section 7 - Handling and Storage**Handling Procedures**

Use protective equipment as described in Section 8 of this safety data sheet when handling uncontained material. Handle in accordance with good industrial hygiene and safety practices.

Storage Procedures

Warehouse storage should be in accordance with package directions, if any. Product should be kept in a cool and dry area in original packaging. Do not freeze.

Section 8 - Exposure Controls / Personal Protection**Exposure Guidelines****A: General Product Information**

Protective equipment should be provided as necessary to prevent inhalation of vapors, prolonged skin contact, and to keep exposure levels below the applicable exposure limits.

B: Component Exposure Limits**Acetone (67-64-1)**

OSHA: 1000 ppm TWA; 2400 mg/m³ TWA

750 ppm TWA; 1800 mg/m³ TWA

ACGIH: 500 ppm TWA

750 ppm STEL

PERSONAL PROTECTIVE EQUIPMENT**Personal Protective Equipment: Eyes/Face**

Safety glasses with side shields or chemical goggles are recommended.

Personal Protective Equipment: Skin

Impervious gloves such as nitrile rubber should be used to help prevent excessive skin contact.

Personal Protective Equipment: Respiratory

A NIOSH approved respirator must be used if vapor concentrations exceed exposure limits.

Ventilation

Local exhaust or general dilution ventilation may be required to maintain exposures below the applicable exposure limits. The need for ventilation systems should be evaluated by a professional industrial hygienist, while the design of specific ventilation systems should be conducted by a professional engineer.

Section 9 - Physical & Chemical Properties

Appearance:	Flammable clear liquid.	Odor:	
Physical State:	Liquid	pH:	5.0-6.0
Vapor Pressure:	828 mbar at 50°C	Vapor Density:	2.0 (air = 1)
Boiling Point:	56°C	Specific Gravity:	0.790
Freezing Point:	-95°C	Viscosity:	0.32 mPa at 20°C
VOC:	<20 g/L		

Section 10 - Stability & Reactivity Information**Stability**

These products are not reactive.

Stability: Conditions to Avoid

Keep away from ignition sources. Do not freeze. Do not thin.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information**Acute Toxicity****A: General Product Information**

Vapors from this product may cause eye and upper respiratory irritation, dry throat and mouth, nausea, headache, dizziness, drowsiness, and coma in extreme cases. Prolonged exposures may lead to liver and kidney injury.

B: Component Analysis - LD50/LC50**Acetone (67-64-1)**

Oral LD50 Rat: 5800 mg/kg

Component Carcinogenicity**Acetone (67-64-1)**

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Section 12 - Ecological Information**Ecotoxicity****A: General Product Information**

No data available for this product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity**Acetone (67-64-1)**

96 Hr LC50 Oncorhynchus mykiss: 4.74-6.33 ml/L; 96 Hr LC50 Pimephales promelas: 6210-8120 mg/L [static]; 96 Hr LC50

Lepomis macrochirus: 8300 mg/L

48 Hr EC50 water flea: 0.0039 mg/L; 48 Hr EC50 water flea: 12700 mg/L [Static]; 48 Hr EC50 Daphnia magna: 12600 mg/L

Section 13 - Disposal Considerations**US EPA Waste Number & Descriptions****A: General Product Information**

This product is classified an ignitable hazardous waste by the Resource Conservation and Recovery Act (RCRA; 40 CFR 261: Waste # D001). Dispose of spilled material in accordance with federal, state, and local regulations in a hazardous waste facility. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch. If you are unsure of the regulations, contact your local Public Health Department, or the local office of the Environmental Protection Agency (EPA).

B: Component Waste Numbers

Acetone (67-64-1)

RCRA: waste number U002 (Ignitable waste)

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - Transport Information**International Transport Regulations**

DOT: UN1090, Acetone, 3, PGII

Flammable Liquid Label Required

Section 15 - Regulatory Information**US Federal Regulations****A: General Product Information**

SARA 311 Status. The following SARA 311 designations apply to this product: Immediate (acute) health hazard. Delayed (chronic) health hazard. Fire hazard.

B: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Acetone (67-64-1)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

State Regulations**A: General Product Information**

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS #	CA	FL	MA	MN	NJ	PA
Acetone	67-64-1	Yes	No	Yes	Yes	Yes	Yes

A: TSCA Status

This product and its components are listed on the TSCA 8(b) inventory.

None of the components listed in this product are listed on the TSCA Export Notification 12(b) list.

B: Component Analysis - Inventory

Component	CAS #	TSCA	DSL	EINECS
Acetone	67-64-1	Yes	Yes	Yes

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Acetone	67-64-1	1 %

WHMIS Classification

Controlled Product Classification: B2, D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations. This SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information**Other Information**Prepared for:
Johns Manville
Roofing Systems
P. O. Box 5108
Denver, CO USA 80217-5108Prepared by:
Johns Manville Technical Center

Material Name: JM Single Ply Cleaner Low VOC**Safety Data Sheet
ID: 3306**

P.O. Box 625005
Littleton, CO USA 80162-5005

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Date	MSDS #	Reason
04/03/09	3306-1.0000	New SDS for new product.
04/03/09	3306-1.0001	Updated VOCs to <20 g/L
04/06/09	3306-1.0002	Trade name change to JM Single Ply Cleaner Low VOC

End of Sheet 3306