

**JS773 AF OFF-WHITE 54 US GL**

Version 1.1

Print Date 09/11/2006

REVISION DATE: 09/01/2006

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : JS773 AF OFF-WHITE 54 US GL  
 Product code : 931100 254

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

**SECTION 2 - HAZARDS IDENTIFICATION**
**Emergency Overview**

Off-White. Paste. No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract.  
 Eyes : Slightly irritating.  
 Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : Irritant effect may be delayed.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

**SECTION 3 - PRODUCT COMPOSITION**

| Chemical Name                            | CAS-No.    | Weight %    |
|--|------------|-------------|
| Clay                                     | 1332-58-7  | 40.0 - 70.0 |
| Calcium Carbonate (Limestone)            | 1317-65-3  | 15.0 - 40.0 |
| Polybutene                               | 9003-29-6  | 7.0 - 13.0  |
| Residual oils (petroleum)                | 64742-62-7 | 5.0 - 10.0  |
| Stoddard solvent (Mineral Spirits)       | 8052-41-3  | 3.0 - 7.0   |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | 1.0 - 5.0   |
| Titanium dioxide                         | 13463-67-7 | 1.0 - 5.0   |

**JS773 AF OFF-WHITE 54 US GL**

Version 1.1

Print Date 09/11/2006

REVISION DATE: 09/01/2006

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Do not use in confined or poorly ventilated areas. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protection equipment**

**JS773 AF OFF-WHITE 54 US GL**

Version 1.1

Print Date 09/11/2006

REVISION DATE: 09/01/2006

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : General ventilation is sufficient.

**Exposure Limits**

| <b>Chemical Name</b>                     | <b>CAS Number</b> | <b>Regulation</b>  | <b>Limit</b>  | <b>Form</b>   |
|--|-------------------|--|---|---|
| Clay                                     | 1332-58-7         | ACGIH TWA:<br>OSHA PEL:<br>OSHA PEL:<br>OSHA TWA:<br>OSHA TWA:               | 2 mg/m3<br>15 mg/m3<br>5 mg/m3<br>15 mg/m3<br>5 mg/m3             | Respirable fraction.<br>Total dust.<br>Respirable fraction.<br>Total dust.<br>Respirable fraction.                          |
| Calcium Carbonate (Limestone)            | 1317-65-3         | OSHA PEL:<br>OSHA PEL:<br>ACGIH TWA:<br>ACGIH TWA:<br>OSHA TWA:<br>OSHA TWA: | 5 mg/m3<br>15 mg/m3<br>3 mg/m3<br>10 mg/m3<br>15 mg/m3<br>5 mg/m3 | Respirable fraction.<br>Total dust.<br>Respirable particles.<br>Inhalable particles.<br>Total dust.<br>Respirable fraction. |
| Stoddard solvent (Mineral Spirits)       | 8052-41-3         | ACGIH TWA:<br>OSHA PEL:  | 100 ppm<br>2,900 mg/m3  |   |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7        | ACGIH TWA:<br>OSHA TWA:<br>OSHA TWA:<br>OSHA PEL:<br>OSHA PEL:               | 0.05 mg/m3<br>0.1 mg/m3<br>0.3 mg/m3<br>15 mg/m3<br>5 mg/m3       | Respirable fraction.<br>Respirable.<br>Total dust.<br>Total dust.<br>Respirable fraction.                                   |
| Titanium dioxide                         | 13463-67-7        | ACGIH TWA:<br>OSHA PEL:<br>OSHA TWA:<br>OSHA TWA:                            | 10 mg/m3<br>15 mg/m3<br>15 mg/m3<br>5 mg/m3                       | Total dust.<br>Total dust.<br>Respirable fraction.  |

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Paste
- Color : Off-White
- Odor : Petroleum Naptha
- pH : Not available.
- Vapour pressure : Not available.

**JS773 AF OFF-WHITE 54 US GL**

Version 1.1

Print Date 09/11/2006

REVISION DATE: 09/01/2006

|                     |   |                  |
|---------------------|---|------------------|
| Vapor density       | : | Heavier than air |
| Melting point/range | : | Not available.   |
| Freezing point      | : | Not available.   |
| Boiling point/range | : | 400 °C, 752 °F   |
| Water solubility    | : | Negligible       |
| Specific Gravity    | : | 1.56             |
| % Volatile Weight   | : | 6 %              |

**SECTION 10 - REACTIVITY / STABILITY**

|                          |   |   |
|--------------------------|---|---|
| Substances to avoid      | : | Oxidizing agents.   |
| Stability                | : | Material is stable under normal storage, handling, and use. |
| Hazardous polymerization | : | Will not occur under normal conditions.                     |

**SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage and disposal requirements under RCRA. Dispose of in a contained chemical landfill in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.  
SARA 311/312 Hazards : Acute Health Hazard  
Chronic Health Hazard

**JS773 AF OFF-WHITE 54 US GL**

Version 1.1

Print Date 09/11/2006

REVISION DATE: 09/01/2006

OSHA Hazardous Components :

|  |            |
|--|------------|
| Clay                                     | 1332-58-7  |
| Calcium Carbonate (Limestone)            | 1317-65-3  |
| Stoddard solvent (Mineral Spirits)       | 8052-41-3  |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |
| Titanium dioxide                         | 13463-67-7 |

OSHA Status: Considered : Irritant  
 hazardous based on the Carcinogen  
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 98 g/l  
 exempt solvent)

VOC Method 310 : 5 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:**

|                       |  |            |
|-----------------------|--|------------|
| MASS RTK Components : | Clay                                     | 1332-58-7  |
|                       | Calcium Carbonate (Limestone)            | 1317-65-3  |
|                       | Stoddard solvent (Mineral Spirits)       | 8052-41-3  |
|                       | Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |
|                       | Titanium dioxide                         | 13463-67-7 |

|                       |  |            |
|-----------------------|--|------------|
| Penn RTK Components : | Clay                                     | 1332-58-7  |
|                       | Calcium Carbonate (Limestone)            | 1317-65-3  |
|                       | Polybutene                               | 9003-29-6  |
|                       | Residual oils (petroleum)                | 64742-62-7 |
|                       | Stoddard solvent (Mineral Spirits)       | 8052-41-3  |
|                       | Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |
|                       | Titanium dioxide                         | 13463-67-7 |

|                     |  |            |
|---------------------|--|------------|
| NJ RTK Components : | Clay                                     | 1332-58-7  |
|                     | Calcium Carbonate (Limestone)            | 1317-65-3  |
|                     | Polybutene                               | 9003-29-6  |
|                     | Residual oils (petroleum)                | 64742-62-7 |
|                     | Stoddard solvent (Mineral Spirits)       | 8052-41-3  |
|                     | Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:  
 14808-60-7 Crystalline Silica (Quartz)/ Silica Sand

**JS773 AF OFF-WHITE 54 US GL**

Version 1.1  
 REVISION DATE: 09/01/2006

Print Date 09/11/2006

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

|              |   |
|--------------|---|
| Health       | 2 |
| Flammability | 1 |
| Reactivity   | 0 |
| PPE          |   |

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT - Department of Transportation  
 DSL - Domestic Substance List  
 EPA - Environmental Protection Agency  
 HMIS - Hazardous Materials Information System  
 IARC - International Agency for Research on Cancer  
 MSHA - Mine Safety Health Administration  
 NDSL - Non-Domestic Substance List  
 NIOSH - National Institute for Occupational Safety and Health  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 RTK - Right To Know  
 SARA - Superfund Amendments and Reauthorization Act  
 STEL - Short Term Exposure Limit  
 TLV - Threshold Limit Value  
 TSCA - Toxic Substances Control Act  
 TWA - Time Weighted Average  
 V - Volume  
 VOC - Volatile Organic Compound  
 WHMIS - Workplace Hazardous Materials Information System